

SIMATIC S7-1500, DIGITAL INPUT MODULE, DI 16xDC 24V BA, 16 CHANNELS IN GROUPS OF 16; INPUT DELAY TYP. 3.2MS; INPUT TYPE 3 (IEC 61131) INCL. FRONT CONNECTOR PUSH-IN



General information	
Product type designation	DI 16 x 24 V DC BA
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13 / V13
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision 	V1.0 / V5.1
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> DI 	Yes
<ul style="list-style-type: none"> Counter 	No
<ul style="list-style-type: none"> MSI 	Yes
Supply voltage	

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Power

Power available from the backplane bus	1.05 W
--	--------

Power loss

Power loss, typ.	1.8 W
------------------	-------

Digital inputs

Number of digital inputs	16
Digital inputs, parameterizable	No
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 3	Yes

Input voltage

<ul style="list-style-type: none"> • Type of input voltage • Rated value (DC) • for signal "0" • for signal "1" 	DC 24 V -30 to +5V +11 to +30V
---	---

Input current

<ul style="list-style-type: none"> • for signal "1", typ. 	2.7 mA
--	--------

Input delay (for rated value of input voltage)

for standard inputs	
— parameterizable	No
— at "0" to "1", min.	3 ms
— at "0" to "1", max.	4 ms
— at "1" to "0", min.	3 ms
— at "1" to "0", max.	4 ms

for interrupt inputs

— parameterizable	No
-------------------	----

for counter/technological functions

— parameterizable	No
-------------------	----

Cable length

<ul style="list-style-type: none"> • shielded, max. • unshielded, max. 	1 000 m 600 m
--	------------------

Encoder

Connectable encoders

<ul style="list-style-type: none"> • 2-wire sensor — permissible quiescent current (2-wire sensor), max. 	Yes 1.5 mA
--	---------------

Isochronous mode

Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Diagnostics function	No
Alarms	
• Diagnostic alarm	No
• Hardware interrupt	No
Diagnostic messages	
• Monitoring the supply voltage	No
• Wire-break	No
• Short-circuit	No
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• Monitoring of the supply voltage (PWR-LED)	No
• Channel status display	Yes; Green LED
• for channel diagnostics	No
• for module diagnostics	No
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels, in groups of	16
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
Decentralized operation	
Prioritized startup	Yes
Dimensions	
Width	25 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	230 g

Other

Note:

Supplied incl. 40-pole push-in front connectors

last modified:

12/06/2016