

SIMATIC DP, ELECTRONIC MODULE 2 AO I HIGH FEATURE FOR ET 200S, 15 MM WIDE, CYCLE TIME PER MODULE: 0.5MS, +/- 20MA; 15 BIT + SIGN, 4 .. 20MA; 15 BIT, OPERATIONAL LIMITS +/- 0.05% WITH LED SF (GROUP FAULT)



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	80 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, max.	1.2 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog outputs	
Number of analog outputs	2
Current output, no-load voltage, max.	18 V
Cycle time (all channels) max.	0.5 ms
Output ranges, current	

• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for current output two-wire connection	Yes
• for current output four-wire connection	No
Load impedance (in rated range of output)	
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH
Destruction limits against externally applied voltages and currents	
• Current, max.	50 mA
Cable length	
• shielded, max.	200 m; 100m if $T_{wa} < 2ms$
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
Settling time	
• for resistive load	0.3 ms
• for capacitive load	1 ms
• for inductive load	0.5 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.01 %
Temperature error (relative to output range), (+/-)	0.003 %/K
Crosstalk between the outputs, min.	60 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.01 %
Operational error limit in overall temperature range	
• Current, relative to output range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to output range, (+/-)	0.05 %
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Substitute values connectable	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Group error	Yes

Diagnostics indication LED

- Group error SF (red) Yes

Parameter

Remark	7 byte
Diagnostics wire break	Disable / enable
Output type/range	deactivated / +/-20 mA / 4 to 20 mA
Group diagnostics	Disable / enable
Response to CPU/master STOP	Output current and de-energized/substitute a value/keep last value

Potential separation

Potential separation analog outputs

- between the channels No
- between the channels and backplane bus Yes
- Between the channels and load voltage L+ Yes

Permissible potential difference

between MANA and M internally (UISO)	75 V DC/60 V AC
--------------------------------------	-----------------

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Weights

Weight, approx.	40 g
-----------------	------

last modified: 12/19/2016