

SIMATIC S7-300 DIGITAL INPUT SM321, OPTICALLY ISOLATED  
 IN GROUPS OF 16, 64 DI, DC 24V, 3MS, SINKING/SOURCING  
 TERMINAL BLOCKS 6ES7392-1.N00-0AA0 AND CABLES  
 6ES7392-4...0-0AA0 NECESSARY



<b>Supply voltage</b>	
Load voltage L+	
• Rated value (DC)	24 V
<b>Input current</b>	
from backplane bus 5 V DC, max.	100 mA
<b>Power loss</b>	
Power loss, typ.	7 W
<b>Digital inputs</b>	
Number of digital inputs	64
Input characteristic curve in accordance with IEC 61131, type 1	Yes
<b>Number of simultaneously controllable inputs</b>	
all mounting positions	
— up to 40 °C, max.	64
— up to 60 °C, max.	32
horizontal installation	
— up to 40 °C, max.	64
— up to 60 °C, max.	32

vertical installation	
— up to 40 °C, max.	32
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	13 to 30V
Input current	
• for signal "1", typ.	4.2 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	No
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	No
• Hardware interrupt	No
Diagnostic messages	
• Diagnostic functions	No
• Wire-break	No
Diagnostics indication LED	
• Group error SF (red)	No
• Status indicator digital input (green)	Yes
Potential separation	
Potential separation digital inputs	
• between the channels	No
• between the channels, in groups of	16
• between the channels and the backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	500 V DC

### Connection method

required front connector

Cable: 6ES7 392-4Bxx0-0AA0 terminal blocks: 6ES7 392-1xN00-0AA0

### Dimensions

Width

40 mm

Height

125 mm

Depth

112 mm

### Weights

Weight, approx.

230 g

**last modified:**

03.08.2015