

SIMATIC S7-300, DIGITAL INPUT SM 321, OPTICALLY ISOLATED,  
8 DI, 120V/230V AC, 1 X 20 PIN



Figure similar

<b>Supply voltage</b>	
Load voltage L1	
• Rated value (AC)	230 V; 120/230V AC
<b>Input current</b>	
from backplane bus 5 V DC, max.	29 mA
<b>Power loss</b>	
Power loss, typ.	4.9 W
<b>Digital inputs</b>	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
<b>Number of simultaneously controllable inputs</b>	
horizontal installation	
— up to 60 °C, max.	8
vertical installation	
— up to 40 °C, max.	8

Input voltage	
• Type of input voltage	AC
• Rated value (AC)	230 V; 120/230V AC
• for signal "0"	0 to 40V
• for signal "1"	79 to 264V
• Frequency range	47 ... 63 Hz
Input current	
• for signal "1", typ.	6.5 mA; (120 V); 11 mA (230 V)
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", max.	25 ms
— at "1" to "0", max.	25 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	2 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Diagnostic functions	No
Alarms	
• Diagnostic alarm	No
• Hardware interrupt	No
Diagnostics indication LED	
• Group error SF (red)	No
• Status indicator digital input (green)	Yes
Potential separation	
Potential separation digital inputs	
• between the channels	No
• between the channels, in groups of	2
• between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	4 000 V DC
Connection method	

required front connector	20-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	240 g
<b>last modified:</b>	12/06/2016