

SIMATIC S7-300, ANALOG INPUT SM 331, FLOATING, 8AI, RESOLUTION 9/12/14 BITS, U/I/THERMOCOUPLE/RESISTANCE ALERT, DIAGNOSTICS; 1X20PIN REMOVE/INSERT W. BACKPLANE BUS



Figure similar

| Supply voltage  |  |
|---|--|
| Load voltage L+   |  |
| • Rated value (DC)  | 24 V   |
| • Reverse polarity protection   | Yes  |
| Input current   |  |
| from load voltage L+ (without load), max.                             | 30 mA  |
| from backplane bus 5 V DC, max.                                       | 50 mA  |
| Power loss  |  |
| Power loss, typ.  | 1 W  |
| Analog inputs   |  |
| Number of analog inputs   | 8  |
| • For resistance measurement  | 4  |
| permissible input voltage for voltage input (destruction limit), max. | 20 V; continuous; 75 V for max. 1 s (mark to space ratio 1:20) |
| permissible input current for current input (destruction limit), max. | 40 mA  |

| Input ranges                               |                |
|--|----------------|
| • Voltage                                  | Yes            |
| • Current                                  | Yes            |
| • Thermocouple                             | Yes            |
| • Resistance thermometer                   | Yes            |
| • Resistance                               | Yes            |
| Input ranges (rated values), voltages      |                |
| • 0 to +10 V                               | No             |
| • 1 V to 5 V                               | Yes            |
| • Input resistance (1 V to 5 V)            | 100 k $\Omega$ |
| • 1 V to 10 V                              | No             |
| • -1 V to +1 V                             | Yes            |
| • Input resistance (-1 V to +1 V)          | 10 M $\Omega$  |
| • -10 V to +10 V                           | Yes            |
| • Input resistance (-10 V to +10 V)        | 100 k $\Omega$ |
| • -2.5 V to +2.5 V                         | Yes            |
| • Input resistance (-2.5 V to +2.5 V)      | 100 k $\Omega$ |
| • -250 mV to +250 mV                       | Yes            |
| • Input resistance (-250 mV to +250 mV)    | 10 M $\Omega$  |
| • -5 V to +5 V                             | Yes            |
| • Input resistance (-5 V to +5 V)          | 100 k $\Omega$ |
| • -50 mV to +50 mV                         | No             |
| • -500 mV to +500 mV                       | Yes            |
| • Input resistance (-500 mV to +500 mV)    | 10 M $\Omega$  |
| • -80 mV to +80 mV                         | Yes            |
| • Input resistance (-80 mV to +80 mV)      | 10 M $\Omega$  |
| Input ranges (rated values), currents      |                |
| • 0 to 20 mA                               | Yes            |
| • Input resistance (0 to 20 mA)            | 25 $\Omega$    |
| • -10 mA to +10 mA                         | Yes            |
| • Input resistance (-10 mA to +10 mA)      | 25 $\Omega$    |
| • -20 mA to +20 mA                         | Yes            |
| • Input resistance (-20 mA to +20 mA)      | 25 $\Omega$    |
| • -3.2 mA to +3.2 mA                       | Yes            |
| • Input resistance (-3.2 mA to +3.2 mA)    | 25 $\Omega$    |
| • 4 mA to 20 mA                            | Yes            |
| • Input resistance (4 mA to 20 mA)         | 25 $\Omega$    |
| Input ranges (rated values), thermocouples |                |
| • Type B                                   | No             |
| • Type C                                   | No             |
| • Type E                                   | Yes            |

|  |               |
|--|---------------|
| • Input resistance (Type E)                                | 10 MΩ         |
| • Type J   | Yes           |
| • Input resistance (type J)                                | 10 MΩ         |
| • Type K   | Yes           |
| • Input resistance (Type K)                                | 10 MΩ         |
| • Type L   | Yes           |
| • Input resistance (Type L)                                | 10 MΩ         |
| • Type N   | Yes           |
| • Input resistance (Type N)                                | 10 MΩ         |
| • Type R   | No            |
| • Type S   | No            |
| • Type T   | No            |
| • Type U   | No            |
| • Type TXK/TXK(L) to GOST                                  | No            |
| <b>Input ranges (rated values), resistance thermometer</b> |               |
| • Cu 10  | No            |
| • Ni 100   | Yes; Standard |
| • Input resistance (Ni 100)                                | 10 MΩ         |
| • Ni 1000  | No            |
| • LG-Ni 1000   | No            |
| • Ni 120   | No            |
| • Ni 200   | No            |
| • Ni 500   | No            |
| • Pt 100   | Yes; Standard |
| • Input resistance (Pt 100)                                | 10 MΩ         |
| • Pt 1000  | No            |
| • Pt 200   | No            |
| • Pt 500   | No            |
| <b>Input ranges (rated values), resistors</b>              |               |
| • 0 to 150 ohms  | Yes           |
| • Input resistance (0 to 150 ohms)                         | 10 MΩ         |
| • 0 to 300 ohms  | Yes           |
| • Input resistance (0 to 300 ohms)                         | 10 MΩ         |
| • 0 to 600 ohms  | Yes           |
| • Input resistance (0 to 600 ohms)                         | 10 MΩ         |
| • 0 to 6000 ohms   | No            |
| <b>Thermocouple (TC)</b>                                   |               |
| <b>Temperature compensation</b>                            |               |
| — parameterizable  | Yes           |
| — internal temperature compensation                        | Yes           |

|  |   |
|--|---|
| — external temperature compensation with compensations socket          | Yes   |
| <b>Characteristic linearization</b>                                    |   |
| • parameterizable  | Yes   |
| — for thermocouples  | Type E, J, K, L, N  |
| — for resistance thermometer   | Pt100 (standard, climatic range), Ni100 (standard, climatic range)                                |
| <b>Cable length</b>  |   |
| • shielded, max.   | 200 m; 50 m at 80 mV and thermocouples  |
| <b>Analog value generation for the inputs</b>                          |   |
| Measurement principle  | integrating   |
| <b>Integration and conversion time/resolution per channel</b>          |   |
| • Resolution with overrange (bit including sign), max.                 | 15 bit; Unipolar: 9/12/12/14 bit; bipolar: 9 bit + sign/12 bit + sign/12 bit + sign/14 bit + sign |
| • Integration time, parameterizable                                    | Yes; 2,5 / 16,67 / 20 / 100 ms  |
| • Basic conversion time (ms)   | 3 / 17 / 22 / 102 ms  |
| • Interference voltage suppression for interference frequency f1 in Hz | 400 / 60 / 50 / 10 Hz   |
| <b>Encoder</b>   |   |
| <b>Connection of signal encoders</b>                                   |   |
| • for current measurement as 2-wire transducer                         | Yes   |
| • for current measurement as 4-wire transducer                         | Yes   |
| • for resistance measurement with two-wire connection                  | Yes   |
| • for resistance measurement with three-wire connection                | Yes   |
| • for resistance measurement with four-wire connection                 | Yes   |
| <b>Errors/accuracies</b>   |   |
| <b>Operational error limit in overall temperature range</b>            |   |
| • Voltage, relative to input range, (+/-)                              | 1 %; ±1% (80 mV); ±0.6% (250 mV to 1 000 mV); ±0.8% (2.5 V to 10 V)                               |
| • Current, relative to input range, (+/-)                              | 0.7 %; From 3.2 to 20 mA  |
| • Resistance, relative to input range, (+/-)                           | 0.7 %; 150, 300, 600 Ohm  |
| • Resistance thermometer, relative to input range, (+/-)               | 0.7 %; +/-0.7% (Pt100/ Ni100); +/-0.8% (Pt100 climate)  |
| <b>Basic error limit (operational limit at 25 °C)</b>                  |   |
| • Voltage, relative to input range, (+/-)                              | 0.6 %; ±0.4 % (250 mV to 1 000 mV); ±0.6 % (2.5 mV to 10 mV); ±0.7 % (80 mV)                      |
| • Current, relative to input range, (+/-)                              | 0.5 %; 3.2 to 20 mA   |
| • Resistance, relative to input range, (+/-)                           | 0.5 %; 150, 300, 600 Ohm  |
| • Resistance thermometer, relative to input range, (+/-)               | 0.6 %; ±0.5% (Pt100/ Ni100), ±0.6% (Pt100 climate)  |

| Interrupts/diagnostics/status information |  |
|---|--|
| Diagnostic functions                      | Yes; Parameterizable                   |
| Alarms                                    |  |
| • Diagnostic alarm                        | Yes; Parameterizable, channels 0 and 2 |
| • Limit value alarm                       | Yes; Parameterizable                   |
| Diagnostic messages                       |  |
| • Diagnostic information readable         | Yes                                    |
| Diagnostics indication LED                |  |
| • Group error SF (red)                    | Yes                                    |
| Potential separation                      |  |
| Potential separation analog inputs        |  |
| • between the channels and backplane bus  | Yes                                    |
| Isolation                                 |  |
| Isolation tested with                     | 500 V DC                               |
| Connection method                         |  |
| required front connector                  | 20-pin                                 |
| Dimensions                                |  |
| Width                                     | 40 mm                                  |
| Height                                    | 125 mm                                 |
| Depth                                     | 117 mm                                 |
| Weights                                   |  |
| Weight, approx.                           | 250 g                                  |
| <b>last modified:</b>                     | 12/07/2016                             |