

SIMATIC S7, ANALOG INPUT SM336 6 AI; 15 BIT; FAILSAFE ANALOG INPUTS FOR SIMATIC SAFETY, WITH HART SUPPORT, UP TO CATEGORY 4 (EN954-1)/ SIL3 (IEC61508)/PLE (ISO13849), 1 X 20 PIN,



Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
From power supply L+, typ.	150 mA
from backplane bus 5 V DC, max.	90 mA
Power loss	
Power loss, typ.	4.5 W
Analog inputs	
Number of analog inputs	6
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	No
• Current	Yes
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	150 Ω; typ. 150 ohms max. 175 ohms

• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	150 Ω; typ. 150 ohms max. 175 ohms
Cable length	
• shielded, max.	1 000 m

Analog value generation for the inputs

Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 15 bit + sign
• Integration time (ms)	20 ms @ 50 Hz, 16.7 ms @ 60 Hz
• Interference voltage suppression for interference frequency f1 in Hz	$f=n \times (f1\pm 0.5\%)$

Encoder

Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes

Errors/accuracies

Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.2 %; 40 μA
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %

Interrupts/diagnostics/status information

Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
• Encoder supply Vs (green)	No

Potential separation

Potential separation analog inputs	
• between the channels	Yes
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes

Isolation

Isolation tested with	370V for 1 min
-----------------------	----------------

Standards, approvals, certificates

Highest safety class achievable in safety mode	
--	--

- acc. to EN 954
- SIL acc. to IEC 61508

4
SIL 3

Connection method

required front connector 20-pin

Dimensions

Width 40 mm
Height 125 mm
Depth 120 mm

Weights

Weight, approx. 350 g

last modified: 12/10/2016