

SIMATIC S7-300, CP341 COMMUNICATION PROCESSOR WITH RS232C INTERFACE (V.24) INCL. CONFIG. PACKAGE ON CD



Figure similar

Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>• 24 V DC</li> </ul>	Yes
Input current	
from supply voltage L+, max.	100 mA
from backplane bus 5 V DC, max.	70 mA
Power loss	
Power loss, typ.	1.6 W
Power loss, max.	2.4 W
Interfaces	
Number of interfaces	1; Isolated
Interface physics, RS 232C (V.24)	Yes
Transmission rate, min.	0.3 kbit/s
Transmission rate, max.	115.2 kbit/s
Point-to-point	
<ul style="list-style-type: none"> <li>• Cable length, max.</li> </ul>	15 m

<ul style="list-style-type: none"> <li>supported printers</li> </ul>	Serial printers
<ul style="list-style-type: none"> <li>Connector type</li> </ul>	9-pin sub D connector
<b>Integrated protocol driver</b>	
— 3964 (R)	Yes
— ASCII	Yes
— RK512	Yes
<b>Telegram length, max.</b>	
— 3964 (R)	4 096 byte
— ASCII	4 096 byte
— RK 512	4 096 byte
<b>Transmission speed, RS 232</b>	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
— with RK 512 protocol, max.	115.2 kbit/s
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Software</b>	
<b>Block</b>	
• FB length in RAM, max.	6 100 byte; Data communication, sending and receiving
<b>Connection method</b>	
Power supply	3 screw-type terminals: L+, M, GND
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	300 g
<b>last modified:</b>	12/10/2016