

SIMATIC DP, CM PROFIBUS DP FOR ET 200SP CPU MODULE WITH PROFIBUS DP INTERF. (9 PIN SUB-D, FEMALE) DP-MASTER FOR 125 DP-SLAVES



General information	
Product type designation	ET 200SP, CM DP
HW functional status	FS01
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13 Update 3
Installation type/mounting	
Rack mounting possible	No
Rail mounting possible	Yes; Standard - DIN rail
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Interfaces	
Number of PROFIBUS interfaces	1
1. Interface	

Interface types	
• RS 485	Yes
Functionality	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• SIMATIC communication	Yes
Interface types	
RS 485	
• Transmission rate, max.	12 Mbit/s
• Cable length, max.	100 m
Protocols	
PROFIBUS DP master	
Services	
— PG/OP communication	Yes
— S7 routing	Yes
— Data record routing	Yes
— Isochronous mode	No
— Equidistance	No
— Number of DP slaves	125
— Activation/deactivation of DP slaves	Yes
PROFIBUS DP slave	
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes
• Address area, max.	120
• User data per address area, max.	128 byte
Services	
— PG/OP communication	Yes; Only with active interface
— Routing	Yes; Only with active interface
— S7 communication	Yes; Only with active interface
— Direct data exchange (slave-to-slave communication)	Yes; No subscriber possible - only passive publisher
— DPV1	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnostics indication LED	
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	

between backplane bus and interface	Yes
-------------------------------------	-----

Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C

Dimensions

Width	35 mm
Height	117 mm
Depth	75 mm

Weights

Weight, approx.	80 g
last modified:	12/22/2016